Patent Claims

- 1. Shower head arrangement,
 - 1.1 with a flat profile (1),
 - 1.2 with which the rear side (2) is formed for support on a wall surface,
 - 1.3 with a concealed fitting,
 - 1.4 which is located in the section on the rear side (2) of the profile (1),
 - 1.5 which is covered by the profile (1) and
 - 1.6 which can be activated from the front side of the profile, and
 - 1.7 with at least one shower head (8).
- 2. Shower head arrangement according to claim 1, with which the fittings may be fixed on the profile (1).
- 3. Shower head arrangement according to claim 1 or 2, with a concealed box (7) enclosing the fittings (20, 21, 22, 23).
- 4. Shower head arrangement according to claim 3, with which the concealed box (7) may be fixed on the profile (1).
- 5. Shower head arrangement according to one of the preceding claims, with which the side extension of the concealed box (7) and/or the concealed fittings (20, 21, 22, 23) is smaller than the width of the profile (1).
- 6. Shower head arrangement according to one of the preceding claims, with which the fittings (22, 23) partly extend into the profile (1).
- 7. Shower head arrangement according to according to one of the preceding claims, with a shower handset and a holding bracket for the latter that is connected by means of a hose (12).

- 8. Shower head arrangement according to claim 7, with which the water delivery to the shower handset passes through the interior of the profile (1) through a channel formed inside the profile and/or through a hose.
- 9. Shower head arrangement according to one of the preceding claims, with at least a side shower head (8).
- 10. Shower head arrangement according to one of the preceding claims, with several fittings which are concealed or if necessary are separately operable side shower heads (8).
- 11. Shower head arrangement according to one of the preceding claims, with clamped-joint connections for the hydraulic connection of the piping of the profile with the fittings.
- 12. Shower head arrangement according to one of the preceding claims, with a fitting connected with the profile, which can connect clamped-joint connections with the house installation.